





URM III Series

URM III 2.9 Pro

Product features:

- Click-lock — true single-person installation.
- Automatic — comprehensive corner protection.
- Curve range — (Convex) $-10^{\circ} \sim +10^{\circ}$ (Concave)
- Pinch n' go module — high efficiency of screen maintenance



Main Technical Specifications:

Parameter	URM III 2.9 Pro
Pixel Pitch	2.9mm
LED Type	3-in-1 Black SMD
Brightness	1.000 cd/m ²
Pixel Density	112,896 pixels/m ²
Pixels Per Panel	168×336 pixels
Module Size	W250mm×H250mm
Panel Size	W500mm×H1,000mm×D71mm
Weight	12.5 kg/panel
Maintenance	Front & Rear
Ingress Protection	IP30
Curve	(Convex) -10°~+10°(Concave)
Aspect Ratio	1:2
Panel Area	0.5 m ²
Recommended Viewing Distance	≥2.9m
Environment	Indoor
Material	Die-cast Aluminum
Calibration	Support Brightness and Chroma
Brightness Control	Manual/Automatic
Color Temperature	2,000K~9,300K Adjustable
Horizontal Viewing Angle	160°
Vertical Viewing Angle	160°
Contrast Ratio	3,000:1
Input Power <Max>	240 W/panel
Input Power <Typical>	70 W/panel
Input Voltage	100~240 VAC
Processing Depth	16 bit

Scan Method	1/21
Refresh Rate	7,680@60 Hz
Video Frame Rate	23~240 Hz
Input Power Frequency	50~60 Hz
LED Life Time	100,000 Hours
Operating Temperature/Humidity	-10°C~+45°C/10~80%RH
Storage Temperature/Humidity	-20°C~+50°C/10~60%RH
Standard Mounting Configuration	Hanging, Stacking
Certification	TUV-CE/CB/FCC/IC/UL

Note:

1. The image of the product above is for illustration only and may differ from the actual product (including but not limited to appearance, color, size, etc.).
2. The parameters are reference values, part of which is obtained under a specific test environment in Unilumin' s internal laboratory, there may be slight differences in actual use due to differences in product batch, configuration, software versions, use conditions, and environmental factors.