



Udesign SV Series

Udesign SV3.9 Holographic Screen

Product features:

- 92% High Permeability, No Building Lighting Affect;
- Ultra-Thin Design, Cost Saving;
- Easy Attached to Glass Surface, Efficient & Convenient Installation and Maintenance;
- Flexible Screen, Supported Cutting, Bending, Suitable for Various Installation Environment.

SPECIFICATION PARAMETERS:

Specification	Udesign SV3.9		
Pixel Pitch	3.9 mm		
Visual Permeability	92%		
LED Type	SMD Integrated LED & IC		
Pixel Density	65,536 dot/m ²		
Module Size	250 x 1025 mm	250 x 1197 mm	250 x 1500 mm
Display Size	250 x 1000 mm	250 x 1172 mm	250 x 1469 mm
Pixel per Module	64 x 256 dots	64 x 300 dots	64 x 376 dots
Brightness	2500 nits (Black lamp)		2000 nits (Black lamp)
	4500 nits (White lamp)		3000 nits (White lamp)
Driving Mode	Constant Current Driving		

Refresh Rate	≥ 3840Hz (Static)
Weight	6 kg/m ²
Input Power	AC 100-240 V 50/60Hz
Color Temperature	3000~10000 K
Frame Rate	60~120 Hz
Scanning Mode	Static Driving (Single Pixel Single Control)
Gray Scale	16 bit
Peak Power Consumption	865 W/m ²
Typical Power Consumption	350 W/m ²
Installation Method	LED Side Glued PCB Side Glued Hanging Up
Maintenance Method	Front
Ingress Protection	IP20
Operating Temperature/Humidity	-20°C ~ 50°C/20% -85% (Without Condensation)
Storage Temperature/Humidity	-20°C ~ 60°C/10% -85% (Without Condensation)

Note:

1. Product pictures are for illustration only, the actual product effects (including but not limited to appearance, color, size) may be slightly different, please refer to the actual product;
2. The specification parameters are reference values. Data comes from Unilumin's internal laboratory and is obtained under a specific test environment. Actually, it may be slightly different due to product batch differences, configuration differences, software versions, use conditions & environmental factors. Actual usage shall prevail.