



Umake OF Series

Umake OF1.5 Sphere Screen

Product Features:

- 3840Hz High Refresh Rate, No Screen Flicker
- 240W/m² Low Power Consumption, Cost Saving
- Seamless Design, Smooth Display Screen
- Magnetic Design, Efficient Installation

SPECIFICATION PARAMETERS:

Specification	Umake OF1.5	
Diameter (m)	1	1.5
Area (m ²)	3.14	7.07
Pixel Pitch	1.5 mm	
LED Type	SMD	
Resolution (Overall)	2094x1046	3140x1570
Module Seam	≤0.25 mm	
Module Installation Method	Magnet	
Weight	40 kg/m ²	
Contrast Ratio	4500:1	
Brightness	≥600 nits	
Refresh Rate	3840 Hz	
Gray Scale	14 bit	

Color Temperature	5500-9500 K (Adjustable)
Peak Power Consumption	720 W/m ²
Typical Power Consumption	240 W/m ²
Viewing Angle	(H)160°/(V)140°
Input Voltage	AC100V~240V
Operating Voltage	DC4.2V~4.6V
Ingress Protection	IP31
Installation Method	Front
Maintenance Method	Lifting/Fixing
Operating Temperature/Humidity	-10°C~+45°C/10~80%RH (No Freeze)
Storage Temperature/Humidity	-20°C~+55°C/10~85%RH (No Freeze)

Note:

1. Product pictures are for illustration only, the actual product effects (including but not limited to appearance, color, size) may be slightly different, please refer to the actual product;
2. The specification parameters are reference values. Part of the data comes from Unilumin's internal laboratory and is obtained under a specific test environment. In actual use, it may be slightly different due to product batch differences, configuration differences, software versions, use conditions and environmental factors. Actual usage shall prevail.